

MATERIAL COMPOSITION:

Recycled granulate bound using a PU binding agent and possibly a colouring agent

SIZE:

sizes: 540 x 540 mm

half: 540 mm x 255 mm

corner: 255 mm x 255 mm

thickness: 15 and 20 mm

Size tolerance

± 2%

± 5%

COLOURS:

black

red

green

grey



COLOURFASTNESS:

The product is not colourfast and the colour may change due to influences of the weather and walking on the rubbertiles

CARBON BLACK:

Carbon black is a black colouring agent which exists in every rubber tile and which can come out due to influences of the weather

QUICKLIME/CEMENT VEILING:

Due to weather influences and quicklime/cement veiling of the surrounding objects the tiles might develop a white efflorescence

GUARANTEE:

3 year guarantee for wear-resistance, when used home, garden and gyms. The guarantee does not apply to colour

GRANULAT:

fine 0,7 - 1 mm

standard 1 - 3 mm

DENSITY:

800 kg/m³, 900 kg/m³ en 1.000 kg/m³

WATER PERMEABILITY:

920 mm/h EN 12616

FIRE RESISTANCE:

Efl to EN 13501

SMOKE RESISTANCE:

S2

INSULATION VALUE:

Rd 0,15 EN13165

U 3,13 EN 6946

SOUND ATTENUATION:

ΔLw 25 DB

SLIP RESISTANCE:

R10

