


INERTIA

Length: 594cm
Width: 328cm
Height: 233cm
Weight: 1398.6kg
Load: 110kg in each pulley



ANTICORROSION PAINT TREATMENT

Three-layer paint treatment with anticorrosion primer.



3MM THICK STRUCTURE

Structure with a thickness of 3mm made of high-durability ST-37/40 quality steel and a 5mm thick coated steel cable.



SEATS WITH INJECTION CORE

Seats with injection core and ergonomic design. They ensure a correct body position and prevent deformations in the padding and the proliferation of bacteria.



VISUAL SCALE WITH DIDACTIC WEIGHT INDICATORS IN 3 COLORS ACCORDING TO LOAD LEVEL

A highly intuitive system that helps the user quickly identify the load and its evolution or progression in the exercise.



GRAPHIC EXERCISE PANEL

Explanatory graphic panel illustrating the different exercises that can be performed and the muscles targeted.

CARACTERÍSTICAS TÉCNICAS

- Designed for optimum exercise biomechanics. To guarantee smooth, natural movements for
- full muscle concentration.
- Calibrated weights. For guaranteed weight person.
- High resistance 5 mm and 6 mm thick coated Steel cable, for smooth, secure performance.
- Hard chrome guides and IGUS drylining bushing. Offering a silent, sliding action and minimum maintenance. The bushings are resistant to friction and to high temperatures.
- 360° free hold, for a more natural exercise, adapted to the anatomical movement of the arms of each particular user, whilst maintaining control. Controlled mobility.
- Magnetic weight plate selectors. The magnets ensure that there is no possibility of the selector coming out during training.
- Stainless steel components. Designed to offer long-lasting durability.
- Use of laser cutting technology, for optimum tube cutting precision.
- Structure of 3 mm thick ST-37/40 steel frame and pulley support plates of 8 mm thick steel frame. Offers guaranteed durability.
- Multiple training positions at the ergoline.
- Weight of exercise adapted to beginners and the most experienced ones.
- Accessories: triceps rope, three short rope grips, two long rope grips and dorsal pull rod.
- Adjustable support in height, in the position of the high pulley with seat.
- Easy access to all elements of control and load selection from the working position of the user.
- Structure raised 50mm above floor level with rubber tipped feet. This provides access for cleaning and vacuuming without scratching the paint.
- Front and rear fairings. Provides greater security to the user during exercise, avoiding accidents while the plates are moving. Easy to clean.
- According to the UNE-EN 957 regulation.
- Legs with rubber protections.
- Positions in each tower: high pulley with seat, double ergoline with adjustable pulley, rowing with short pulley and high pulley without seat.
- Injected core fireproof seat. Unlike the classic foam padded particle boards, the injected core offers the advantage of uniformity, anti-distortion and greater anti-bacterial protection.

Length	594cm
Width	328cm
Height	233cm
Weight	1398.6kg
Load	110 kg in each pulley